



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B60C 11/12, 11/13	A1	(11) International Publication Number: WO 99/48707 (43) International Publication Date: 30 September 1999 (30.09.99)
<p>(21) International Application Number: PCT/US98/05816</p> <p>(22) International Filing Date: 25 March 1998 (25.03.98)</p> <p>(71) Applicant (for all designated States except US): THE GOODYEAR TIRE & RUBBER COMPANY [US/US]; 1144 East Market Street, Akron, OH 44316-0001 (US).</p> <p>(72) Inventor; and</p> <p>(75) Inventor/Applicant (for US only): HEINEN, Richard [BE/LU]; 30, rue de la Charmoye, B-6720 Habay-la-Neuve (BE).</p> <p>(74) Agent: KING, David, L.; The Goodyear Tire & Rubber Company, 1144 East Market Street, Akron, OH 44316-0001 (US).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	
(54) Title: TIRE TREAD AND MOLD FOR MAKING TREADS		
<p>(57) Abstract</p> <p>A tire tread, comprising elastomeric material, has a plurality of grooves therein, defining ground engaging elastomeric elements (1). The elastomeric elements (1) include a sipe extending from the tread surface towards the interior of the elastomeric material, where the sipe has a first surface area (23) and an opposite facing second surface area (24), each surface area (23, 24) has a plurality of recesses (21) or protrusions (20). Each recess (21) has a centroid (25) aligned with a centroid of a protrusion. The combination of recesses (21) and protrusions (20) interlock increasing the rigidity of the elastomeric elements.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

TIRE TREAD AND MOLD FOR MAKING TREADS

Technical field

The present invention relates to sipes for tire treads as well as to pneumatic tires whether new or retreaded including such a tread.

5 Background art.

The tread portion of a pneumatic tire generally comprises a plurality of circumferentially and laterally extending grooves defining ground engaging rubber elements. The particular size and shape of these elements contribute significantly to the overall performance of the tire.

10 Winter type tires as well as all season type tires usually have multiple sipes. A sipe is a groove having a width in the range from about 0.2% to 1% of the tread width, i.e. the arc length of the tread surface in the axial direction, that is, in a plane containing the axis of rotation of the tire. The sipe closes when it is located in the tire footprint, i.e. in the contact patch of the tire tread with a flat surface at zero speed and under normal load and pressure.
15 Such a sipe typically is formed by steel blades inserted into a cast or machined mold or tread ring therefor.

A sipe may extend circumferentially or laterally about the tread in a straight, curved or zigzag manner and may be as deep as the grooves or have a depth, which is even greater than the groove depth. The sipes can pass through the sides of the ribs and tread elements or be
20 confined to their interior. It is known to have the sipes lying in planes which are not perpendicular to tangents to the surface of the tread at their point of intersection; the inclination of the planes defining neighboring sipes can be identical or differ step wise along the tread element length. It is further known to use sipes having a depth, which varies across their length, e.g. so-called hump-blades.

25 The sipes increase the number of biting edges. The local high pressure at each biting edge improves the wiping and digging action of the tread surface, conferring to a tire excellent traction on snow and ice. Furthermore, sipes improve the flexibility of the tread elements without destroying their solidity. The easy relative longitudinal sliding between the opposed faces of a sipe weakens the resistance of the tread elements to flexing in the contact area
30 between tread and road and therefore slows down the heat built-up of the tire; on the other hand this flexing of the tread elements leads to diminished handling performance on dry ground and to reduced braking performance on wet ground.

GB-A- 1.241.908 discloses blades in the form of a plate having a planar edge and an opposing edge provided with at least one projection substantially coplanar with said plate.

35 GB-A- 1.150.295 discloses a tire with a rib having a plurality of sipes formed therein. The opposed sidewalls of each sipe are provided with one or more projections extending therefrom towards the other sidewall.

The aim of the invention is to create a sipe layout for a winter type tire tread having good traction properties on ice and snow covered roads.

40 A further aim of the invention is to provide a sipe layout for a tire tread showing

excellent handling properties.

A still further aim of the invention is to provide a tire having low tread wear.

Disclosure of invention.

The invention provides for a tire tread having elastomeric material, the tread having a plurality of grooves defining ground engaging elastomeric elements. At least one of the elastomeric elements includes a sipe having a first surface area and an opposite facing second surface area. Each surface area has a plurality of recesses or protrusions; each recess has a centroid aligned with a centroid of a protrusion and each protrusion extends from the first or second surface area to interlock with a recess. Each protrusion or recess has at least one radially inner end above the depth of the sipe or radially outer end located below the radially outer surface of the ground engaging element.

The invention provides further for a tire mold with blades having a first surface and an opposing second surface and a plurality of recesses and protrusion extending from the surfaces. Each recess or protrusion has a centroid aligned along an axis and spaced from a centroid of an adjoining recess or protrusion by the blade's thickness.

The invention provides still further for a blade having a first flat surface area and an opposite facing second flat surface. Each flat surface has a plurality of recesses or protrusions; each protrusion extending from the first or second flat surface has a centroid aligned with a centroid of a recess from the opposite flat surface.

To acquaint persons skilled in the art, most closely related to the instant invention, certain preferred embodiments are now described with reference to the annexed drawings. These embodiments are illustrative and can be modified in numerous ways within the spirit and scope of the invention defined in the claims.

Brief description of the drawings.

- Figure 1 is a perspective view of a blade according to the invention;
- Figures 2A, 2B and 2C are schematic fragmentary views of the same tread pattern portion, new and worn to different degrees;
- Figure 3 is a schematic view of an elastomeric tread element according to the invention, cut up at the location of the blade;
- Figure 4 is a view of a blade having a single and Figure 5 multiple recesses or protrusions.
- Figure 6 represents blades where the recesses or protrusions are mixed, either in shape or dimension.
- Figures 7 shows a bent blade having three portions.
- Figures 8 shows blades with recesses or protrusions having different shapes.
- Figures 9A through 9E shows elastomeric tread elements including several sipes according to the invention.
- Figures 10 shows several elastomeric tread elements in a directional tread design, the tread elements including sipes according to the invention.

Detailed description of the invention.

With reference to Figure 1, there is represented a blade 1 according to the invention including a plurality of recesses or protrusions 20, 21. The blade is made of metal, preferably steel and recesses are preferably made into the steel sheet by stamping or embossing. The different recesses 21 on one side of the blade (protrusions 20 on the opposite side), have the same shape and dimension and are arranged along parallel lines Δ_i , which lines are also parallel to the closest portion of the tread surface. The lines Δ_i are equally spaced, and in a same line a recess -on one side of the blade- is followed by a protrusion. It is to be understood that in all the drawings only the portions of the blades protruding from the mold surface and having a shaping effect in the elastomeric material composing the tire have been represented, omitting the portion 3 wherewith the blades are anchored in the mold.

It can of course be envisioned to give the lines Δ_i an inclination ranging between 0 and 30 degrees with respect to the closest portion of the tread surface or to change the inclination of each lines Δ_i in function of its spacing from the tread surface. Furthermore, the dimension of the recesses may be different at different locations in the blades: when the tread element wears down, stiffness of the tread element increases and less interlocking, is required. Consequently, the recesses may be given either a greater lateral spacing or a smaller dimension, when their distance with respect to the surface of the new or as molded tread increases.

With reference to Figure 2A, 2B, 2C, there is represented a single elastomeric tread element 10 of a tread pattern after the vulcanization step, divided into two elastomeric segments 11 and 12 by a single blade according to the invention. The neighboring tread elements or ribs of the tread pattern have not been represented for simplification and clarity. The tread element 10 is shown in different states of wear. As represented in Figure 2A, the tread element 10, unworn, is divided into two rectangular portions defined by the radially innermost portion of the blade 1. Radially innermost means here the portion of the blade which is closest to the mold (not represented) wherein the blade is inserted. The same tread portion shown in Figure 2B, is worn to about 25 % of its original radial height and the radially outer surface of the tread element 10 shows three portions of a circle separated by straight lines. The same tread portion shown in Figure 2C is worn to about 50 % of its original radial height. It appears that the three portions of the circle have an opposite orientation to the one represented in Figure 2B.

Referring to Figure 3, showing the tread element 10 of Figure 2, cut up at the location of the sipe, in a perspective view. The protrusions 20 cooperating with the recesses 21 tend to interlock the adjacent elastomeric segments 11 and 12, whereas the substantially flat surfaces 23 allow a gliding of the adjacent substantially flat surfaces 23. By choosing the ratio of the dimension of the flat surface 23 to the number, location and dimensions of the recesses 21 and protrusions 20, the stiffness of two adjacent elastomeric segments 11, 12 can be adapted to the requirements.

In Figure 4 a blade 42 including one single large recess 41 and in Figure 5 a blade 52

including a large number of small recesses 51 has been represented, it being understood a corresponding numbered projections 40, 50 extend from the opposite face of the blades 42, 52.

In Figure 6, several blades where the recesses 21 or protrusions 20 are mixed, either in shape or dimension, have been represented.

Those skilled in the art of molding will appreciate that a protrusion 20 extending from the surface 23 of a blade 1 will form a recess 21 in the molded elastomeric tread element 10 and correspondingly a recess 21 in a blade 1 will cause a protrusion 20 to be formed in the molded element 10.

Referring to Figure 1 of a blade, each protrusion 20 has a surface area defining its exterior shape. As shown the shapes are hemispherical. The centroid X20 of a hemispherical shape lies along the axis 25 passing through the center of the circular base of the hemisphere to a location about two-thirds from the peak of the hemisphere. This location X20 is the volumetric center of the hemispherical shaped projection 20.

As used herein, centroid means the center of mass; centroidally means passing through the centroids. The centroid of a hemispherical projection as measured along the outer surface is a point in space wherein origin of the radius of curvature lies, similarly for a hemispherical recess, the centroid is found as a point in space wherein the origin of the radius of curvature of the inner surface lies. In a flat blade for a sipe, these centroids are not only aligned but are in fact coincident, thus the same point in space.

The recess 21 similarly is hemispherical in shape and accordingly follows the same mathematical formula to determine its centroid X21. If measured from the first surface area 22, the centroid X21 similarly lies along an axis 25 coincident with the associated projection 20 assuming each recess 21 and projection 20 is measured from the same face of 22 or 24 of the blade 1, then the centroids X20, X21 are exactly coincident or at the same location. Alternatively if the centroids of each aligned recess 21 and projection 20 is measured from an opposing face 23, 24, then the centroids will be aligned on the same axis, but spaced by the thickness (t) of the blades.

As one refers Figures 2B and 2C to the tread elements 10, it is easily appreciated that the alignment of the axis 25 on which each centroid X20 and X21 lies, has the centroids X20 and X21 spaced from the other by the gap formed by the blade. As the tire rolls into the footprint, the gap G closes causing the centroids X20 and X21 to become coincident. The resultant effect is that the element portions 12 and 11 interlock, greatly increasing the rigidity of the element. The movement from flexible elements entering the tires footprints and then increasing stiffness as the tire rolls through the footprint greatly enhances the tire designers ability to change the dynamic stiffness of the element as a function of wear condition and performance requirements.

Figure 6 of blades 61 through 68 show a wide range of combinations of recesses and protrusions that permit the resultant elements 10 to have a range of stiffness variations based on location size and orientation of different combinations of these aligned recesses 21 and

protrusions.

In Figure 7, it is shown that the concept is equally applicable to bent blades 70.

While the preferred embodiment shows the use of hemispherical shaped protrusions and recesses, the concept works with almost any known shape as shown in Figure 8.

5 In Figures 9A through 9D a variety of bent or curved sipes 92, 93, 94 are shown in various tread elements 90. Each element 90 has the inventive use of recesses 21 and protrusions 20 being along coincident axis 25 with centroids X20 and X21 shown on the axis 25 spaced by the gap G of the sipe. As the tire tread element 90 enters the footprint, the gap G closes and the centroids become coincident causing an interlocking engagement of recesses and protrusions. As shown, it is preferable that at least some of protrusions, if not all, extend
10 sufficiently to be at least partially extended into an adjoining recess in the open sipe condition when the tire tread element is not in the contact or footprint patch. This helps insure the elements will properly interlock under load.

Figure 9c shows an elongated elastomeric block 90, which takes its origin close to the
15 equatorial plane EP of the tire and extends to the shoulder 91. The block 90 includes two elongated sipes 92 and 93. The sipes extend from a point close to the equatorial plane to the shoulder 91 and are roughly parallel to the grooves 93 and 94 which grooves cooperate with the shoulder 91 of the tire to delimit the block 90. By choosing a variable lateral recess density in the sipes 92, 93, the stiffness of the block 90 may be varied almost continuously
20 from the equatorial plane EP towards the shoulder 91 of the tire. Close to the shoulder 91 stiff blocks or block portions are of advantage in order to have good handling properties whereas towards the center of the tire less stiff block portions have a lower wear. Consequently, elongated sipes provided with only few recesses towards the center and numerous recesses towards the shoulder are recommended (see in this connection blade 64
25 shown on Figure 6). Furthermore as is well known in the art, heel and toe wear can be reduced by making the portion of the block which leaves the footprint of the tire last less stiff than the portion which leaves the footprint of the tire first. Consequently, in order to allow more flexing of the elastomeric material, sipe 92 should also be molded by a blade having more recesses than the blade molding sipe 93.

30 In Figure 10 a partial tread pattern is shown wherein the tread elements 100, 101, 102, 103, 104, 105 and 106 are arranged in circumferential rows forming a heavily siped directional tread pattern. The sipes 110 employing the recesses 21 and protrusions 20 show a very smooth and simple blading pattern. The number of recesses in the blocks belonging to different rows may be chosen different, so as to have rows of different stiffness; likewise,
35 the siping technology according to the invention allows to confer a laterally varying stiffness to all or some of the blocks. Not until the tread is worn appreciably will the submerged recesses 21 and protrusions 20 be revealed and then only after they have been efficiently providing improved handling performance over thousands of kilometers.

40 While certain representative embodiments and details have been shown for the purpose of illustrating the invention, it will be apparent to those skilled in the art that various changes

and modifications may be made therein without departing from the spirit or scope of the invention.

CLAIMS

1. A tire tread having elastomeric material, the tread having a plurality of grooves defining ground engaging elastomeric elements, the tread characterized by at least one of the elements including a sipe, the sipe extending from the ground engaging elements, the sipe having a first surface area and an opposite facing second surface area, each surface area has a plurality of recesses or protrusions, each recess has a centroid aligned with a centroid of a protrusion, each protrusion extends from the first or second surface area to interlock with a recess, each protrusion or recess having at least one radially inner end above the depth of the sipe or radially outer end located below the radially outer surface of the ground engaging element.
2. The tire tread of claim 1 wherein the recesses and protrusion have a substantially hemispherical shape.
3. A tire tread according to claim 1, wherein at least two of said the recesses and protrusion are arranged along a straight line.
4. A tire tread according to claim 1, wherein the recesses and protrusion arranged along a straight line are equally spaced.
5. A tire tread according to claim 1, wherein at least two of said the recesses and protrusion are arranged along a straight line, said line forming an angle comprised between 0 and 45 degrees with the adjacent surface of the tread.
6. A tire tread according to claim 4, wherein at least some of the recesses and protrusion are arranged along two or more parallel lines.
7. A tire tread according to claim 1, wherein the recesses and protrusion in one sipe have all the same depth relative to the radial height of the element containing the one sipe.
8. A tire tread according to claim 1, wherein there are at least two sipes in a ground engaging elastomeric elements, the recesses and protrusion originating from a substantially flat surface, said flat surface forming an angle comprised between 0 and 30 degrees with the tread surface, at the location where the flat surface cuts the tread surface.
9. A tire tread according to claim 1, wherein there are at least three sipes in a ground engaging elastomeric elements, the sipes having substantially equal lateral spacing.
10. A tire tread according to claim 1, wherein there are at least three sipes in a ground engaging elastomeric elements, the spacing between the sipes closest to the tread grooves, defining the ground engaging elements, being smaller than the spacing between the sipes located towards the center of the elements.
11. A tire tread according to claim 1 wherein the centroids of recesses and the adjoining protrusion are coincident as the sipe is closed when the tire element enters the contact patch under normal load.
12. A tire mold characterized by at least one blade, the blade having a first surface and an opposing second surface and a plurality of recesses and protrusion extending from the surfaces, each recess or protrusion having a centroid aligned along an axis and spaced from a centroid of an adjoining recess or protrusion by the blade's thickness.

13. Blade for a tire mold, the blade having at least a first flat surface area and an opposite facing second flat surface area, each flat surface area having a plurality of recesses or protrusions, each protrusion extending from the first or second flat surface area having a centroid aligned with a centroid of a recess from the opposite flat surface area.

- 5 14. The blade of claim 13 wherein the plurality of projections and recesses are configured in one or more of the following ways to control the vertical and horizontal stiffness of the element to be molded around the blade by (a) varying the relative size of the projections and aligned recesses, (b) varying the quantity of the projections and aligned recesses, (c) increasing or decreasing the size or quantity of projections and aligned recesses along the
10 vertical displacement of the blade, and (d) increasing or decreasing the size or quantity of the projections and aligned recesses along the horizontal displacement of the blade.

1/8




FIG-1






FIG-2A

2/8



3/8




FIG-3

4/8




FIG-4




FIG-5

6/8




FIG-7




FIG-8

7/8




FIG-9A




FIG-9B




FIG-9C




FIG-9D




FIG-9E

8/8




FIG-10

INTERNATIONAL SEARCH REPORT

Intr. Application No

PCT/US 98/05816

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B60C11/12 B60C11/13

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B60C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 01189 A (MICHELIN MICHELIN & CIE ;LAGNIER ALAIN (FR)) 18 January 1996 see page 2, line 12 - page 3, line 11; claims; figures	1-14
X	EP 0 515 349 A (SEMPERIT AG) 25 November 1992 see abstract; claims; figures	1
A	PATENT ABSTRACTS OF JAPAN vol. 018, no. 453 (M-1662), 24 August 1994 & JP 06 143941 A (YOKOHAMA RUBBER CO LTD:THE), 24 May 1994 see abstract	
A	GB 1 241 908 A (UNIROYAL) 4 August 1971 cited in the application	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

8 September 1998

Date of mailing of the international search report

15/09/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Soederberg, J.

INTERNATIONAL SEARCH REPORT

Int lional Application No
PCT/US 98/05816

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 1 150 295 A (DUNLOP) 30 April 1969 cited in the application -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int lional Application No

PCT/US 98/05816

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9601189 A	18-01-1996	FR 2722144 A CA 2190880 A EP 0768958 A FI 970006 A NO 970016 A US 5783002 A	12-01-1996 18-01-1996 23-04-1997 02-01-1997 06-01-1997 21-07-1998
EP 0515349 A	25-11-1992	AT 401160 B AT 102991 A AT 131440 T DE 59204643 D US 5350001 A	25-07-1996 15-11-1995 15-12-1995 25-01-1996 27-09-1994
GB 1241908 A	04-08-1971	AT 303555 B BE 742525 A DE 1959370 A FR 2025124 A US 3608602 A	15-10-1972 02-06-1970 18-06-1970 04-09-1970 28-09-1971
GB 1150295 A	30-04-1969	SE 322832 B DE 1480986 A DE 1538709 A FR 1491822 A GB 1150292 A US 3470404 A US 3511290 A	20-04-1970 08-01-1970 22-01-1970 29-11-1967 30-04-1969 30-09-1969 12-05-1970